AMENDMENTS TO THE CLAIMS

1-6. (Canceled).

7. (Currently Amended) A method of driving an electromagnetic pump, the method

comprising:

conveying a fluid from a pump chamber formed inside a cylinder by housing a plunger

including a permanent magnet inside the cylinder;

passing a current through an aircore electromagnetic coil fitted around the cylinder, and

switching a direction of the current, to reciprocally move the plunger in the axial direction inside

the cylinder; and

flowing a pulse current including a period where a voltage or current value is zero when a

supplied current of the electromagnetic coil is inverted,

wherein a pulse minute current at least 30% of an inverted maximum current, whose

current direction is opposite to that of the current passing through the electromagnetic coil

immediately before flowing the pulse current, flows for a minute time period before the period

where the current value is zero, when a polarity of the applied current of the electromagnetic coil

is inverted.

8. (Canceled)

9. (Currently Amended) A method of driving an electromagnetic pump, the method

comprising:

Reply to Office Action of May 13, 2008

conveying a fluid from a pump chamber formed inside a cylinder by housing a plunger

including a permanent magnet inside the cylinder;

passing a current through an aircore electromagnetic coil fitted around the cylinder, while

switching a direction of the current, to reciprocally move the plunger in the axial direction inside

the cylinder; and

firstly flowing an offset current of no greater than 30% of inverted maximum current,

whose current direction is opposite to that of the current passing through the electromagnetic coil

immediately before flowing the offset current, when a polarity of a supplied current of the

electromagnetic coil is inverted.

10. (Currently Amended) The method of driving an electromagnetic pump according

to Claim 9, wherein before a period where the offset current flows, as period where a minute

current pulse at least 30% of the maximum current flows is set before a period when the offset

current flows.

3 DAB/mrh